

**Einsatz im Bergbau, mit großer Tragtiefe.**

<b>Außen- durchmesser</b>	<b>Kern- durchmesser</b>	<b>Steigung</b>	<b>Außen- durchmesser</b>	<b>Kern- durchmesser</b>
<b>Bolzen mm</b>	<b>Bolzen mm</b>		<b>Mutter mm</b>	<b>Mutter mm</b>
Rd 10	6,700	3,000	10,300	7,000
Rd 12	8,700	3,000	12,300	9,000
Rd 14	10,700	3,000	14,300	11,000
Rd 16	11,600	4,000	16,400	12,000
Rd 18	13,600	4,000	18,400	14,000
Rd 20	15,600	4,000	20,400	16,000
Rd 22	17,600	4,000	22,400	18,000
Rd 25	20,600	4,000	25,400	21,000
Rd 28	23,600	4,000	28,400	24,000
Rd 32	27,600	4,000	32,400	28,000
Rd 36	30,500	5,000	36,500	31,000
Rd 40	34,500	5,000	40,500	35,000
Rd 42	36,500	5,000	42,500	37,000
Rd 45	39,500	5,000	45,500	40,000
Rd 48	42,500	5,000	48,500	43,000
Rd 50	44,500	5,000	50,500	45,000
Rd 53	47,500	5,000	53,500	48,000
Rd 56	50,500	5,000	56,500	51,000
Rd 60	53,400	6,000	60,600	54,000
Rd 63	56,400	6,000	63,600	57,000
Rd 67	60,400	6,000	67,600	61,000
Rd 70	63,400	6,000	70,600	64,000
Rd 75	68,400	6,000	75,600	69,000
Rd 80	73,400	6,000	80,600	74,000
Rd 85	78,400	6,000	85,600	79,000
Rd 90	81,200	8,000	90,800	82,000
Rd 95	86,200	8,000	95,800	87,000
Rd 100	91,200	8,000	100,800	92,000
Rd 106	97,200	8,000	106,800	98,000
Rd 112	103,200	8,000	112,800	104,000
Rd 118	109,200	8,000	118,800	110,000
Rd 125	116,200	8,000	125,800	117,000
Rd 123	121,000	10,000	133,000	122,000
Rd 140	129,000	10,000	141,000	130,000
Rd 150	139,000	10,000	151,000	140,000
Rd 160	149,000	10,000	161,000	150,000
Rd 170	159,000	10,000	171,000	160,000
Rd 180	166,800	12,000	181,200	168,000
Rd 190	176,800	12,000	191,200	178,000
Rd 200	186,800	12,000	201,200	188,000
Rd 212	189,800	12,000	213,200	200,000

# Rundgewinde DIN 20400

Rd 224	210,800	12,000	225,200	212,000
Rd 236	218,400	16,000	237,600	220,000
Rd 250	232,400	16,000	251,600	234,000
Rd 265	247,400	16,000	266,600	249,000
Rd 280	262,400	16,000	281,600	264,000
Rd 300	282,400	16,000	301,600	284,000

