

Sägewinde DIN 514 (fein)

Gewinde- Nenn Durchmesser	Durchmesser Bolzen mm	Durchmesser Kernloch Mutter mm
S 12 x 2	8,528	9,000
S 14 x 2	10,528	11,000
S 16 x 2	12,528	13,000
S 18 x 2	14,528	15,000
S 20 x 2	16,528	17,000
S 22 x 3	16,794	17,500
S 24 x 3	18,794	19,500
S 26 x 3	20,794	21,500
S 28 x 3	22,794	23,500
S 30 x 3	24,794	25,500
S 32 x 3	26,794	27,500
S 34 x 3	28,794	29,500
S 36 x 3	30,794	31,500
S 38 x 3	32,794	33,500
S 40 x 3	34,794	35,500
S 42 x 3	36,794	37,500
S 44 x 3	38,794	39,500
S 46 x 3	40,794	41,500
S 48 x 3	42,794	43,500
S 50 x 3	44,794	39,500
S 52 x 3	46,794	47,500
S 55 x 3	49,794	50,500
S 60 x 3	54,794	55,500
S 65 x 4	58,058	59,000
S 70 x 4	63,058	64,000
S 75 x 4	68,058	69,000
S 80 x 4	73,058	74,000
S 85 x 4	78,058	79,000
S 90 x 4	83,058	84,000
S 95 x 4	88,058	89,000
S 100 x 4	93,058	94,000

