

Whitworth Rohrgewinde DIN ISO 228
BSP (British Standart Pipe)

Rohrgewinde für nicht im Gewinde dichtende Verbindungen (zylindrisch), aussen = G

Gewinde- kennung	Durchmesser Inch	Durchmesser außen mm	Durchmesser Mutter mm	Durchmesser Kernloch mm	Gänge je Inch	Steigung mm
G 1/8"	01. Aug	9,73	8,85	8,80	28	0,907
G 1/4"	01. Apr	13,16	11,89	11,80	19	1,337
G 3/8"	03. Aug	16,66	15,39	15,25	19	1,337
G 1/2"	01. Feb	20,95	19,17	19,00	14	1,814
G 5/8"	05. Aug	22,91	21,13	21,00	14	1,814
G 3/4"	03. Apr	26,44	24,66	24,50	14	1,814
G 7/8"	07. Aug	30,20	28,42	28,25	14	1,814
G 1"	1	33,25	30,93	30,75	11	2,309
G 1 1/8"	1 1/8	37,90	35,58	35,30	11	2,309
G 1 1/4"	1 1/4	41,91	39,59	39,25	11	2,309
G 1 3/8"	1 3/8	44,32	42,00	41,70	11	2,309
G 1 1/2"	1 1/2	47,80	45,48	45,25	11	2,309
G 1 3/4"	1 3/4	53,74	51,43	51,10	11	2,309
G 2"	2	59,61	57,29	57,00	11	2,309
G 2 1/4"	2 1/4	65,71	63,39	63,10	11	2,309
G 2 1/2"	2 1/2	75,18	72,86	72,60	11	2,309
G 2 3/4"	2 3/4	81,53	79,21	78,90	11	2,309
G 3"	3	87,88	85,56	85,30	11	2,309
G 3 1/4"	3 1/4	93,98	91,66	91,50	11	2,309
G 3 1/2"	3 1/2	100,33	98,01	97,70	11	2,309
G 3 3/4"	3 3/4	106,68	104,30	104,00	11	2,309
G 4"	4	113,03	110,71	110,40	11	2,309

